

FEATURES



FEATURES

SIZE: 88mm x 19mm

LENGTH: 5.4m

TIMBER: Radiata Pine

GRADE: Finger Jointed –Tight knot grade

TREATMENT: H3.2 CCA –Exterior above ground

FINISH: Smooth all faces –2mm pencil round corners

END USE: Exterior above ground applications non structural

WARRANTY: 50 Year Limited Warranty against rot and decay

QUALITY PRODUCTS

For the past 60 years Taranakipine products have been marketed and distributed in New Zealand and several international markets including Australia, North America and Europe.

We are proud of the reputation we have established in all these markets for quality products manufactured here in New Zealand.



OUR BRANDS



www.taranakipine.co.nz



www.bodyguardwood.com



www.taranakipine.co.nz/products



www.woodspan.co.nz

Physical address:

Hudson Rd, Bell Block,
New Plymouth

Postal address:

PO Box 7145
Fitzroy,
New Plymouth 4341

Contact:

Ph: 06 755 9000
Fax: 06 759 4942

Email: enquiries@taranakipine.co.nz

Website: www.taranakipine.co.nz



FINGERJOINTED EXTERIOR SCREENING AND BASEBOARDS

PREMIUM GRADE RADIATA PINE
AVAILABLE IN SET LENGTH 5.4M

50 YEAR DURABILITY WARRANTY
FROM WELL MANAGED FORESTS



For more about our range of products visit us at

www.taranakipine.co.nz

Taranakipines 88 x 19mm Finger jointed treated boards are an ideal low-cost product for your fencing, screening, and baseboard needs.

Less likely to bow than solid timber and available in 5.4 metre lengths meaning less joints and waste. Treated with H3.2 CCA for outdoor above ground applications, it can be painted or stained.



HANDLING

Product should be kept dry instore and onsite prior to construction.

When storing on site, stack on timber bearers a minimum of 100mm off the ground and keep protected from the weather with a tarpaulin.

Do not stand on the boards prior to installing.

Note: This product is not designed for load-bearing construction such as decking or steps.

FOR BEST RESULTS

Although Taranakipines 88 x 19 Finger Jointed treated boards will last for many years, we recommend for you to coat the boards with a high-quality exterior paint or stain, to achieve a premium finish.

We recommend using 10g x 2"/50mm decking screws for fixing.

Predrill fixing holes at ends of boards to avoid splitting. The span between posts should not be more than 1.2m.

Apply at least two coats of stain or paint to the manufacturer's specification and remember that darker colours will require much more frequent maintenance.

If you do not paint or stain the boards it will not affect the durability of the product, however by choosing to use a good quality stain or paint and maintain it over the life of the product you will retain the high-quality look.

This product will release moisture after installation, causing it to shrink back to 88mm in width. Please allow for this when setting out gaps between boards.



MAINTENANCE

The boards should be maintained the same way as you would outdoor decking or furniture. Between seasons, wash the boards with a nonabrasive detergent using a soft brush or broom. Follow the washing process by hosing off the detergent and allowing it to dry. DO Not use a water blaster or hard brush to clean the boards. (always refer and comply with the coating supplier's recommendations).